


Merkur[®] Seal Repair Kits

406771D

For Model LW075A (75 cc) Merkur Displacement Pump

ENG






Ref. Description		Qty.
4	SPRING, throat	1
6	GLAND, male, throat	1
7	PACKING, throat, UHMWPE	3
8	PACKING, throat, PTFE	2
9	GLAND, female, throat	1
10	SPRING, piston	1
11	GLAND, male, piston	1
12	PACKING, piston, UHMWPE	3
13	PACKING, piston, PTFE	2
14	GLAND, female, piston	1
18	O-RING, piston, 0.9 in (23 mm) OD	1
19	PACKING, throat, reinforced PTFE	5
20	PACKING, piston, reinforced PTFE	5
21	O-RING, lower cylinder, 2.0 in. (51 mm) OD	1
25	O-RING, lower cylinder, 1.9 in. (48 mm) OD	1
26	O-RING, inlet check, 0.75 in. (19 mm) OD	1
27	O-RING, wet cup, 1.4 in. (36 mm) OD	1
28	O-RING, wet cup, 1.7 in. (43 mm) OD	1
33	O-RING, outlet fitting, 0.59 in. (14.9 mm) OD	1

TIP: Some o-rings are close in size. Stack on bench to differentiate.


Standard Seal Repair Kit 24A253



Lubricate Packings

Optional Reinforced PTFE Seal Kit 24J854

Use with materials that cause chemical compatibility concerns with UHMWPE, such as acid catalyst materials.



Lubricate Packings

All written and visual data contained in this document reflects the latest product information available at the time of publication.

Graco reserves the right to make changes at any time without notice.

Original instructions. This manual contains English. MM 406771

Graco Headquarters: Minneapolis International Offices: Belgium, China, Japan, Korea